

### UNSTOPPABLE · UNBEATABLE · NOTHING STANDS IN THE WAY









# DUMP TRAILER STANDARD FEATURES

- 2-Way Combo Gate (Barn Door & Spreader)
- Heavy Duty Ramps (Not on Deck Over Models)(5)
- Wall Mount D-Ring Tie Downs
- Ratchet Style Load Tarp w/Protective Shield LED
- Lights
- 2–5/16" Adjustable Coupler
- 7k Square Drop Leg Jack
- Spare Tire Mount
- Premium High Gloss Powder Coat Finish
- Hydraulic Cylinder Scissor Lift (6.8 models only)



Spare Tire Mount (Shown with Optional Spare Tire)



2-5/16" Adjustable Coupler and HD 7k Drop Leg Jack



5 HD Wall Mount D-Ring Tiedowns

Load Tarp w/Protective Shield



Heavy Duty Ramps







2-Way Combo Gate - Barn Door and Spreader





Barn Door

Spreader



## DUMP TRAILER OPTIONAL FEATURES

- Additional 5,000 lb. Floor Mount D-Rings
- Side Tie-Down Rails
- Spare Tire (TA2, TA3, TA4, & TA5)
- Under-body Storage (6.8 models only)
- Telescoping Cylinder
- Slipper Spring Axles (7K only)
- 8 Watt On-Board Charger



Hydraulic Cylinder Scissor Lift (Standard on 6.8 models only)



COLOR OPTIONS

## HYDRAULIC DUMP TRAILER SPECIFICATIONS

MODEL	H D L 5 1 0 T A 2	H D S 6 1 0 T A 3	H D S 6 1 2 T A 3	HDLPS610TA3	HDLPS612TA3	HDL6812TA4	HDL6814TA5
Total Length	14'	14'	16'	14'	16'	16'2"	18'2"
Total Width	6'6"	6'4"	6'4"	7'10"	7'10"	8'6"	8'6"
Bed Length	10'	10'	12'	10'	12'	12'	14'
Bed Width	5'	6'	6'	6'	6'	6'10"	6'10"
Deck Height	17"	29"	29"	25″	25"	21″	21"
Sides	18"/ 10ga.Steel	18"/ 10ga.Steel	18"/ 10ga.Steel	18"/ 10ga.Steel	18"/ 10ga.Steel	21"/ 10ga. Steel	21"/ 10ga. Steel
Floor	10ga. Steel	10ga. Steel	10ga. Steel	10ga. Steel	10ga. Steel	10ga. Steel	10ga. Steel
Frame	2" x 5" Tube	2" x 6" C-Channel	2" x 6" C-Channel	2" x 6" C-Channel			
G.V.W.R.	7,000 lbs	9,800 lbs	9,800 lbs	9,800 lbs	9,800 lbs	12,000 lbs	14,000 lbs
Empty Weight	2,300 lbs	2,850 lbs	3,050 lbs	2,950 lbs	3,150 lbs	3,500 lbs	3,700 lbs
Payload	4,700 lbs	6,950 lbs	6,750 lbs	6,850 lbs	6,650 lbs	8,500 lbs	10,300 lbs
Cylinders	(1) 3.5" Pwr. Up/Dn	(1) 3.5" Pwr. Up/Dn	(1) 3.5" Pwr. Up/Dn	(1) 3.5" Pwr. Up/Dn	(1) 3.5" Pwr. Up/Dn	Scissor Lift	Scissor Lift
Spring Axles	(2) 3,500lb 4" Drop	(2) 5,200lb Straight	(2) 5,200lb Straight	(2) 5,200lb Straight	(2) 5,200lb Straight	(2) 6,000lb 4" Drop	(2) 7,000lb 4" Drop
Brakes	(2) Electric	(2) Electric	(2) Electric	(2) Electric	(2) Electric	(2) Electric	(2) Electric
Tires	ST205/75R15LRC	ST225/75R15LRD	ST225/75R15LRD	ST225/75R15LRD	ST225/75R15LRD	ST235/80R16LRE	ST235/80R16LRE
<b>Coupler Size</b>	Adjustable 2-5/16"	Adjustable 2-5/16"	Adjustable 2-5/16"	Adjustable 2-5/16"	Adjustable 2-5/16"	Adjustable 2-5/16"	Adjustable 2-5/16"
Jack	7,000 lbs	7,000 lbs	7,000 lbs	7,000 lbs	7,000 lbs	7,000 lbs	7,000 lbs
Stake Pockets	6	6	6	6	6	6	6
5,000 lb. D-Rings	5	5	5	5	5	5	5
Ramps	Pair	N/A	N/A	Pair	Pair	Pair	Pair
Dump Gate	2-Way Combo Gate	2-Way Combo Gate	2-Way Combo Gate	2-Way Combo Gate	2-Way Combo Gate	2-Way Combo Gate	2-Way Combo Gate





Inside Tool Box

Slipper Spring Axle (6.8 models only)





# FORCE

#### WARRANTY INFORMATION

Every trailer is covered by a 1 Year limited warranty depending on model/or brand. The terms or conditions of this warranty will be included with each trailer's certificate of origin. You will receive these documents when a trailer is paid in full. The warranty period will begin on the date of retail sale. Please fill out the registration card when you purchase the trailer and return it to Forest River, Inc. All information contained in this brochure is believed to be accurate at the time of publication. However, during the model year, it may be necessary to make revisions and Forest River, Inc., reserves the right to make all such changes without notice, including prices, colors, materials, equipment and specifications as well as the addition of new models and the discontinuance of models shown in this brochure. Therefore, please consult with your Forest River, Inc., dealer and confirm the existence of any materials, design or specifications that are material to your purchase decision.

©2020 Force a Division of Forest River, Inc., a Berkshire Hathaway Company. All Rights Reserved